

HEAVY DUTY FRICTION STAYS



PRODUCT DESCRIPTION

Designed for commercial applications, the Duration Heavy Duty Friction Stays are suitable for all materials, from uPVC, to timber and aluminium. They are available in top and side hung versions, and come in a choice of sizes. Tested to 50,000 cycles, these heavy duty friction stays are made to last, and will ensure the smooth operation of large casement windows.

FEATURES & BENEFITS

- Available in both top hung and side hung variants
 - Side hung sizes: 12" and 16"
 - Top hung sizes: 16", 20" and 24"
- Available in both 14mm and 17mm stack heights
 - Tested to 50,000 cycles
- Manufactured from stainless steel
 - Sold in pairs
- Superior weather and draught proofing
 - 10 year mechanical guarantee

HEAVY DUTY FRICTION STAYS

	SIZE (INCHES)	OPEN ANGLE (°)	MAX WEIGHT (KG)	MAX VENT SIZE (MM - W x H)
SIDE HUNG	12"	88°	25	600 x 1000
	16"	84°	30	800 x 1000
TOP HUNG	16"	52°	28	1000 x 600
	20"	43°	32	1200 x 700
	24"	39°	42	1200 x 750

14MM STACK HEIGHT



17MM STACK HEIGHT



PACKAGING

Boxed in 25 pairs.

MAINTENANCE

To maintain a high quality appearance and operation we recommend that all external hardware is cleaned routinely, and moving parts are lightly lubricated a minimum of twice a year. Products used within a 1 mile radius of coastal areas, building sites or large industrial areas, more regular cleaning will be required to prevent build up of corrosive contaminants.