

# 2500EA / 5000EA


*Acoustic window ventilator*

## Physical specification


All measurements in millimetres unless otherwise indicated

**Materials:** Aluminium Alloy

## 2500EA Acoustic



External



Internal

## 2500EA Acoustic slot size


**Height:** 13mm

Length
192mm


## Installation

1. Prepare the window frame with the correct slot sizes.
2. Use the self tapping screws to install the acoustic parts.
3. Use standard pyramid vent screws to install the canopy and vent.

## 5000EA Acoustic



External



Internal

## 5000EA Acoustic slot size

**Height:** 13mm

Length	Central gap	Length
172mm	10mm	172mm

The best of both worlds... achieves Building Regulations' EA requirements along with fantastic acoustic performances up to 45dB(A)



### Features and benefits


- Smallest acoustic window vents providing 2500mm<sup>2</sup> or 5000mm<sup>2</sup> equivalent area ventilation on the market
- Achieves the best acoustic performance for window ventilators available within the UK – up to 45dB(A)
- A simple, yet adaptable, solution to meet required specification/Building Regulation requirements incorporating both high levels of equivalent area ventilation and acoustic noise reduction
- Modularity of acoustic sets provides flexibility for installation and acoustic performance
- Aesthetically pleasing design which is easy to open and control by the homeowner
- Excellent airtightness performance with upward air deflection to reduce the risk of draughts
- May require add on section in some window installations

### Sets comprise of:

- 1 EA vent + 1 external acoustic module** – providing noise reduction with discreet internal aesthetics.
- 1 EA vent + 2 acoustic modules** (for internal and external install) – providing maximum noise reduction.

### Performance


#### 2500EA acoustic performance



#### Key

2500EA.W.AC1      2500EA.W.AC2

#### 5000EA acoustic performance



#### Key

5000EA.W.AC1      5000EA.W.AC2

### Models, control options and key data

Product code	Description	Controls	Acoustic performance				Colour
			Dn,e,w	Dn,e,w (C)	Dn,e,w (Ctr)	Equivalent area mm <sup>2</sup>	
2500EA.W.AC1 *	Vent + 1 Acoustic External Module	Front	42dB(A)	41dB	40dB	2670	White
2500EA.W.AC2 *	Vent + 2 Acoustic Modules	Front	45dB(A)	43dB	42dB	2670	White
5000EA.W.AC1 *	Vent + 1 Acoustic External Module	Front	39dB(A)	38dB	37dB	5350	White
5000EA.W.AC2 *	Vent + 2 Acoustic Modules	Front	42dB(A)	40dB	38dB	5350	White