

DURATION



STANDARD FRICTION STAYS

PRODUCT DESCRIPTION

Suitable for most uPVC, aluminium and timber windows, the Duration Standard Friction Stays are available in a variety of sizes for both top and side hung applications. Delivering excellent weather and draught proofing, these friction stays are also easy to fit and built to last, ensuring long service life and smooth operation of the window.

FEATURES & BENEFITS

- Available in both top and side hung variants
 - Side hung sizes: 12" and 16"
 - Top hung sizes: 8", 10", 12", 16", 20" and 24"
- Available in both 13mm and 17mm stack heights
 - Tested to 25,000 cycles
 - Manufactured from stainless steel
 - Sold in pairs
- Superior weather and draught proofing
 - 10 year mechanical guarantee
 - Secured by Design accredited



DURATION



STANDARD FRICTION STAYS

	SIZE (INCHES)	OPEN ANGLE (°)	MAX WEIGHT (KG)	MAX VENT SIZE (MM - W x H)
SIDE HUNG	12"	60°	24	600 x 1200
	16"	87°	28	650 x 1200
TOP HUNG	8"	68°	12	1200 x 300
	10"	60°	16	1200 x 450
	12"	66°	21	1200 x 600
	16"	62°	25	1200 x 750
	20"	42°	30	1200 x 900
	24"	38°	45	1200 x 1200

13MM STACK HEIGHT



17MM STACK HEIGHT



PACKAGING

Boxed in 25 pairs.

MAINTENANCE

To maintain a high quality appearance and operation we recommend that all external hardware is cleaned routinely, and moving parts are lightly lubricated a minimum of twice a year. Products used within a 1 mile radius of coastal areas, building sites or large industrial areas, more regular cleaning will be required to prevent build up of corrosive contaminants.